
1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION

Brand Name..... MANUS-BOND 30-A, 30-A S.L., 65-A
Product Use Adhesive / Sealant
Product Identification Number UN 3175

MANUFACTURER

Manus Products, Inc.
866 Industrial Blvd West
Waconia, MN 55387

EMERGENCY TELEPHONE NUMBER

CHEMTREC: 800-424-9300

Plant Telephone: 952 442-3323

2. COMPOSITION/INFORMATION ON INGREDIENTS

	CHEMICAL NAME	CAS NUMBER	WEIGHT %
	Calcium Carbonate	7317-65-3	<10
	Xylene	1330-20-7	<40
	Carbon Black	1333-86-4	<1
	Ethyl Benzene	100-41-4	<10
	Titanium Dioxide	13463-67-7	<10

See Section 15 of this MSDS for OSHA Regulatory Status

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Heavy paste with petroleum odor; various colors: aluminum, white, black and beige.

Flammable liquid (contains xylene). Inhalation can cause nausea, anesthesia, ringing in the ears, central nervous system effects. Can cause skin and eye irritation. In case of fire, use foam, dry chemical, CO₂.

POTENTIAL HEALTH EFFECTS

PRIMARY ROUTE(S) OF ENTRY

Inhalation (breathing); eye and skin contact.

WARNING! Inhalation can cause nausea, anesthesia, ringing in the ears, central nervous system effects. Can cause skin and eye irritation.

SYMPTOMS OF EXPOSURE

Inhalation: Breathing vapors can be irritating to the nose and throat. Inhalation of high concentrations can result in nausea, vomiting, headache, ringing in the ears. Can cause anesthetic effects and act as a central nervous system depressant.

Eye Contact: Vapors cause eye irritation; contact may cause severe irritation, eye damage.

Skin Contact: Can cause loss of natural oils, dermatitis. Symptoms may include redness, drying and cracking of skin. May be absorbed through skin.

Ingestion: May cause burning sensation in mouth and stomach, nausea, vomiting and salivation.

CHRONIC EFFECTS

May be harmful to fetus, kidneys, liver, or central nervous system.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Eye or skin disease, breathing or respiratory disorders. Intentional misuse by deliberately concentrating and inhaling vapors can be harmful or fatal.

REPORTED AS CARCINOGEN OR POTENTIAL CARCINOGEN

_ Not Applicable

_ National Toxicology Program (NTP)

_ OSHA

3 International Agency for Research on Cancer (IARC)
(See Section 11)

4. FIRST AID MEASURES

Inhalation: Remove from area to fresh air. If not breathing, clear airway and start mouth-to-mouth artificial respiration or use a bag-mask respirator. Get immediate medical attention. If victim is having trouble breathing, transport to medical care and, if available, give supplemental oxygen.

Eye contact: Immediately rinse eyes slowly and gently with water for at least 15 minutes while holding eyelids apart to ensure rinsing of the entire surface of the eyes and lids with water. Remove any contact lenses after the first 5 minutes and then continue flushing eyes. Get immediate medical attention.

Skin Contact: Wash affected areas with large amounts of running water, and soap if available, for 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing and decontaminate shoes before reuse.

Ingestion: **DO NOT** induce vomiting. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention.

NOTE TO PHYSICIAN

Chemicals of exposure are Xylene, Toluene and Ethyl Benzene which are irritants to eyes, skin, mucous membranes, respiratory and gastroesophageal tracts.

5. FIRE FIGHTING MEASURES

Flash Point and Method..... 80 °F. (Xylene)

GENERAL HAZARD

This product and its vapors are flammable. Explosive in a contained area. Vapors are heavier than air and may travel along the ground or may be moved by ventilation. Vapors may be ignited by open flames, sparks, heaters, smoking, electric motors or other sources of ignition distant from use.

EXTINGUISHING MEDIA

For small fires, use foam, CO₂, or dry chemical. For large fires, use water spray, fog, or foam.

SPECIAL FIREFIGHTING INSTRUCTIONS

Move containers from area if it can be done without risk.

FIREFIGHTING EQUIPMENT

As in any fire, wear NIOSH approved, positive-pressure self-contained breathing apparatus and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Wear appropriate protective equipment (See Section 8). Ventilate area. Determine whether spill notification must be made to the appropriate authorities. Observe all local, state and federal regulations.

7. HANDLING AND STORAGE

HANDLING

Wear appropriate protective equipment (See Section 8). Avoid contact with eyes, skin and clothes. Avoid breathing vapors. Keep container closed when not in use. Use with sufficient ventilation to keep area below established exposure levels. Wash thoroughly after handling.

Product and product vapors are flammable.

STORAGE

Keep container tightly closed. Store in a flammable material area. Isolate from incompatible materials (see Section 10).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Use local exhaust or general dilution ventilation system.

PERSONAL PROTECTION

Respirator: For exposures above the established limits, use a NIOSH approved respirator that has been selected by an industrial hygienist or other technically qualified person for the specific work conditions. If respirators are used, OSHA requires compliance with its respiratory protection program (29 CFR 1910.134).

Eye Protection: Wear vented safety goggles.

Gloves: Wear gloves impervious to xylene, toluene and ethylbenzene, such as SilverShield or 4H.

Clothing: Wear clothing that will protect the skin from exposure to this chemical. During emergency or while making repairs, wear clothing that will not allow this chemical to penetrate.

Other: Eye wash; safety shower.

EXPOSURE CONTROLS

COMPONENT	OSHA PEL		ACGIH TLV	
	TWA	STEL	TWA	STEL
Magnesium Oxide, Total Particulates*	15 mg/m ³	N/E	N/E	N/E
Calcium Carbonate, Total Particulates*	15 mg/m ³	N/E	10 mg/m ³	N/E
Respirable Fraction*	5 mg/m ³			
Xylene	100 ppm	N/E	100 ppm	150 ppm
Carbon Black*	3.5 mg/m ³	N/E	3.5 mg/m ³	N/E
Ethyl Benzene	100 ppm	125 ppm	100 ppm	125 ppm
Titanium Dioxide*	15 mg/m ³	N/E	10 mg/m ³	N/E

* Exposure limits are provided for information only. These chemicals are not in a respirable form in this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

State	Paste	Vapor Density	Heavier than air
Color	N/A	Reactivity in Water	Negligible
Odor	Petroleum	Specific Gravity	1.05 – 1.19
Melting Point °F	>300	Water Solubility	Negligible
Boiling Point	N/E	pH.....	NA
Vapor Pressure (mm Hg).....	7.1(calculated)		

10. STABILITY AND REACTIVITY

REACTIVITY

Stable.

INCOMPATIBILITIES

Avoid contact with strong acids, caustic materials and oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS

May form oxides of carbon and various unidentified organic compounds.

CONDITIONS TO AVOID

Avoid temperatures above 120 °F.

11. TOXICOLOGICAL INFORMATION

For Titanium Dioxide

Trochimowicz, *et al.*, *J. Appl. Tox.*, **8**, 383-385 (1988).

Oral LD ₅₀ (rat)	>25 g/kg
Dermal LD ₅₀ (rabbit)	>10 g/kg
Inhalation LC ₅₀ (rat)	>6.82 mg/l (4 hr)

E.I. DuPont's Haskel Toxicology Laboratory conducted lifetime inhalation studies of respirable titanium dioxide at levels up to 250 mg/m³; no compound related clinical signs of toxicity were seen in the exposed animals. Slight pulmonary fibrosis was seen at 50 to 250 mg/m³ respirable titanium dioxide but not at 10 mg/m³. There was no evidence of cancer in animals exposed to 10 or 50 mg/m³ respirable titanium dioxide. Microscopic lung tumors

were seen in 17 percent of the rats exposed to 250 mg/m³ respirable titanium dioxide. The lung tumors observed in the rats were different from common human lung cancers, relative to anatomic type and location, and occurred only at dust levels which overwhelmed the animals lung clearance mechanism and therefore, are of questionable biological relevance for man.

Results of a DuPont epidemiology study showed that employees who had been exposed to titanium dioxide pigments were at no greater risk of developing lung cancer than were employees who had not been exposed to titanium dioxide pigments. No pulmonary fibrosis was found in any of the employees and no associations were observed between titanium dioxide pigment exposure and chronic respiratory disease or lung abnormalities. Based on the results of this study, DuPont concluded that titanium dioxide pigment will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.

The National Cancer Institute (NCI) conducted a feed study in rats and mice in which either 25,000 or 50,000 parts per million titanium dioxide was given in their diet for two years. Under the condition of the NCI test, titanium dioxide did not cause cancer by the oral route.

Titanium dioxide has been classified by the American Congress of Governmental Industrial Hygienists (ACGIH) as an A4 Carcinogen - *Not Classifiable as a Human Carcinogen*. ("1999 TLVs and BEIs," p. 67). It has been classified by the International Agency for Research on Cancer (IARC) as Group 3 - *Not Classifiable as to Its Carcinogenicity to Humans*. (IARC Monograph 47, 1989).

For Product: None for Product

For Carbon Black: IARC – Group 2B (Possibly carcinogenic to humans)

For Ethyl Benzene: ACGIH – A3-confirmed animal carcinogen; BEI

12. ECOLOGICAL INFORMATION

For Product: None for Product

For Xylene: LC50 (96 hr) fathead minnow: 16.1 mg/L.
..... LC50 (96 hr) rainbow trout: 8.05 mg/L.

For Ethyl Benzene: LC50 (96 hr) fathead minnow: 12.1 mg/L.
..... LC50 (96 hr) rainbow trout: 14.0 mg/L.

13. DISPOSAL CONSIDERATIONS

RCRA Waste Code:.....Not Regulated.

Do not allow material to enter sewer systems. Observe all applicable federal, state, and local regulations.

14. TRANSPORT INFORMATION

DOT Proper Shipping NameSolids containing flammable liquids, n.o.s., (Xylene)
DOT Hazard Class.....4.1 (Flammable Solid)
DOT I.D. Number.....UN 3175
Packing Group.....II
Label(s).....Flammable Solid
NAERG - Guide No.133

15. REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

Hazardous Non-Hazardous

CERCLA/SUPERFUND (40 CFR 117, 302)

Chemical Name	RQ (lbs)/(kg)
Xylene	100 lb. / 45.4 kg
Toluene	1000 lb. / 454 kg
Ethyl Benzene	1000 lb. / 454 kg

SARA EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355)

Chemical Name	TPQ (lbs)	RQ (lbs)
N/A	N/A	N/A

SARA HAZARD CATEGORIES (40 CFR 370)

Acute Chronic Fire Pressure Reactive None

SARA TOXIC CHEMICALS (40 CFR 372)

Chemical Name	CAS Number	%
Xylene	1330-20-7	< 40
Ethylbenzene	100-41-4	<10

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (CPR Section (33))

This product has been classified according to the hazard criteria of the Controlled Products Regulations, and the MSDS contains all required information.

Controlled Product; Classification: B4, D2A, D2B Not a Controlled Product

INVENTORY STATUS

The ingredients of this chemical are listed on the US TSCA Chemical Substance Inventory and the Canadian Domestic Substances List.

TOXIC SUBSTANCES CONTROL ACT

No specific regulations apply.

STATE REGULATIONS

Florida Hazardous Substance List Xylene, Ethyl Benzene
 Massachusetts Right to Know List Xylene, Ethyl Benzene, Carbon Black, Titanium Dioxide
 Minnesota Hazardous Substance List Xylene, Ethyl Benzene, Carbon Black, Titanium Dioxide
 New Jersey Right to Know List Xylene (SN 2014), Ethyl Benzene (SN 0851), Carbon Black (SN 0342), Titanium Dioxide (SN 1861)
 Pennsylvania Right to Know List Xylene, Ethyl Benzene, Carbon Black, Titanium Dioxide
 Rhode Island Hazardous Substance List Xylene, Ethyl Benzene, Carbon Black, Titanium Dioxide
 California Proposition 65 Toluene, Benzene, Formaldehyde, Crystalline Silica

16. OTHER INFORMATION

ABBREVIATIONS

C - Ceiling limit

LC_{Lo} - The lowest concentration of a substance in air that will kill a test animal within a certain exposure period.

LC₅₀ - The concentration of a substance in air that will kill 50% of test animals within a certain exposure period.

LD₅₀ - The dose that causes death in 50% of test animals.

N/A - Not applicable

N/D - Not determined

N/E - Not established

N/K - Not known

NAERG - North American Emergency Response Guidebook

RQ - Reportable Quantity

TPQ - Threshold Planning Quantity

PREPARATION INFORMATION

Prepared by: Manus Chemical Safety and Health Department

MSDS No.: MANUS-BOND 30-A, 30-A S.L., 65-A (White, gray, black)

Date Prepared: November 11, 2009

Date of Issue: November, 2009

Supersedes: November, 2006

REVISION INFORMATION

Section 8: Modified Respirator information. Added ACGIH STEL for xylene, and OSHA respirable limit for calcium carbonate.

Section 15: Corrected information for SARA Toxic Chemicals.