

MANUS-BOND 76AMC SELF-LEVELING CONCRETE FLOOR JOINT SEALANT

1. PRODUCT DESCRIPTION:

Manus-Bond 76AMC Self-Leveling Floor Joint Sealant is a one-component, flexible sealant engineered for contraction/expansion joints and cracks in concrete floors and decks. 76AMC flows smoothly and easily into concrete joints and cracks providing a permanent, durable seal. The “controlled flow” technology of 76AMC offers a fast and efficient application. This product is highly UV resistant and does not contain solvents or isocyanates. USDA accepted.

Conforms to the following specifications:

- ASTM C920, Type S, Grade P, Class 25, Use T and M
- Federal Specification TT-S-00230C, Type 1, Class A
- CAN/CGSB-19.13-M87, Class C-1-40-B-N and C-1-25-B-N

2. TECHNICAL DATA:

Specific Gravity	1.63-1.66
Viscosity (cps) (Spindle T-E @ 5 rpms)	100,000-120,000cps
Skin time	20-45 minutes
% Elongation	400%
Shore A	25
Tensile Strength	200psi
Shrinkage	Nil
Low temperature flexibility	Properties retained to -75°F
Staining	Non-staining
UV Ratings (ASTM G-26)	After 2000 hours UV-A no change in appearance or physical properties

3. PACKAGING:

10.3 fl.oz. cartridges and sausage packs; 20 fl.oz. sausage packs; 29 fl.oz. cartridges; quart cans; 1, 5 and 50 gallon containers.

4. SURFACE PREPARATION:

Apply to clean, dry surfaces free of contaminants that can adversely affect adhesion. Remove all old sealant before applying 76AMC. Testing a small area for compatibility is recommended.

5. PAINTING:

Cured product may be painted with most industrial & consumer paints. Testing prior to painting is recommended.

6. STORAGE LIFE:

12 months. For maximum shelf life, store unopened product at or below 80°F.

7. PRECAUTIONS:

Use with adequate ventilation. Inhalation of vapor during application and cure may cause slight eye or throat irritation. In case of contact with eyes, lips, or mouth, flush thoroughly with water. If irritation persists, consult a physician. Avoid repeated, prolonged contact with skin. See MSDS for additional information. **KEEP OUT OF REACH OF CHILDREN.**


8. TECHNICAL SERVICE:

Manus technical representatives are always available to provide assistance. Please contact our Technical Service Department with your questions or requests for specific applications.

9. LIMITED WARRANTY:

Any goods proved defective will be replaced or the purchase price refunded. The limited warranty described herein is in lieu of any other warranty, expressed or implied, including any implied warranty of merchantability or fitness for a particular use. The user shall determine suitability of the product for its intended use. Liability for any incidental or consequential damage or loss is excluded. The user assumes all risks of the product's use, handling and storage.

Distributed by



MANUS PRODUCTS, INC.

866 INDUSTRIAL BLVD. WEST • WACONIA, MINNESOTA 55387
PHONE (952) 442-3323 • FAX (952) 442-3327
www.manus.net • info@manus.net

NAPLES, FL • BEVERLY HILLS, MI